

TECHNICAL FABRIC DETAILS

BUVEL



Buvel is a velvet with high friction resistance providing enormous longevity. With a panoply of colors this article is recommended for upholstery.



Article specification

Width	138 cm
Horizontal repeat cm	Plain
Vertical repeat cm	Plain
Composition	100% POL
Weight	396 g/m ²
Thickness (mm)	1.300

Cleaning Instructions



Use Code

Curtains

Accessories

Upholstery

Bed covering

Environmental Standards

ISO 14001

OEKO TEX STANDARD 100

PFC-FREE

PROP 65

FR Standards

AATCC 96 Complies

CAL 117

NFPA 260

BS5852 Source 0

FMVSS 302

Finish

Anti-bacterial/microbial

Odour resistant

PFC free

Mildew resistant

Stain free technology

Optional Fabric Treatment

Mechanical Performance

Abrasion Test / Martindale Rubs (EN ISO 12947-1,2)	100.000
Piling Test (EN ISO 12945-2)	4
Colour Fastness to light (ISO 105-B02-2)	4-5
Colour fastness to dry rub (EN ISO 105-X12)	Dry: 4-5 Wet: 4-5
Tearing strength (ISO 13937-3)	Warp: 57N Weft: 97 N
Tensile Strenght (EN ISO 13934-1)	Warp: 1200 Weft: 970
Colour fastness to artificial weathering (ISO 105-B04)	
Seam slippage (ISO 13936-2)	Warp: 2 Weft: 2
Colour fastness to chlorinated water (ISO 105-E03)	
Ultraviolet protection factor UPF (AZ/NZS 4399/1996)	
Spray test (ISO 24920)	
Shrinkage to washing (ISO 5077:2007)	Warp: Weft:
Water column mm (ISO 20811)	



Damaceno & Antunes
Rua da Alegria 387,
4475-310 Milheirós - Maia
+351229059160 info@damaceno-antunes.pt