

TECHNICAL SPECIFICATIONS SHEET

LOOPING

| DESCRIPTION | STANDARD | UNT | VALUE |
|------------------------------------|------------------------------------|-------------------|-------------------------|
| Total Weight | TS 1534-2 EN ISO 2286-2 | GR/M ² | 800+ %10 |
| Thickness | TS 1534-2 EN ISO 2286-3 | MM | 1.15+ %10 |
| Width | | CM | 140 cm ± 2cm |
| Tensile Strenght Horizontal | TS EN ISO 1421:1998 | N | 45 |
| Tensile Strenght Vertical | TS EN ISO 1421:1998 | N | 52 |
| Color Fastness To Light | Light Color ISO 105-B02 ISO 4892-2 | bw | 5-6 |
| Color Fastness To Light | Dark Color ISO 105-B02 ISO 4892-2 | bw | 5-6 |
| Flexing Endurance | -5º TS EN ISO 5402-1 | flx | 90.000 |
| Martindale Abrasion | 12kPa TS EN ISO 12947-2 | rub | 90.000 |
| Phtalate Free | En 15777 | | * |
| Composition | %2PU-%78PVC-%20 SUEDE BACKING | | |
| Extention&Recovery | Warp | % | 10,6% 2 |
| Extention&Recovery | Weft | % | 23,5% 1 |
| Flame retardant | Normative | | UNE 1021 1/2 BS 5852 |