

TECHNICAL FABRIC DETAILS

ALISI




The Alisi curtain combines functionality and safety in one product. With a width of 300 cm, it is perfect for covering large window surfaces, offering a continuous and sophisticated appearance. Made from 100% polyester with an FR acrylic coating, this blackout curtain ensures complete light blockage and added fire resistance, making it ideal for any setting requiring both darkness and safety.

Article specification

Width	300 cm
Horizontal repeat cm	PLAIN
Vertical repeat cm	PLAIN
Composition	100%POL + FR ACR COATING
Weight	385 g/m ²
Thickness (mm)	

Cleaning Instructions



Use Code

Curtains

Environmental Standards

FR Standards

EN 13773

Finish

Optional Fabric Treatment

Mechanical Performance

Abrasion Test / Martindale Rubs (EN ISO 12947-1,2)	
Piling Test (EN ISO 12945-2)	
Colour Fastness to light (ISO 105-B02-2)	4
Colour fastness to dry rub (EN ISO 105-X12)	Dry: Wet:
Tearing strength (ISO 13937-3)	Warp: Weft:
Tensile Strenght (EN ISO 13934-1)	Warp: Weft:
Colour fastness to artificial weathering (ISO 105-B04)	
Seam slippage (ISO 13936-2)	Warp: Weft:
Colour fastness to chlorinated water (ISO 105-E03)	
Ultraviolet protection factor UPF (AZ/NZS 4399/1996)	
Spray test (ISO 24920)	
Shrinkage to washing (ISO 5077:2007)	Warp: Weft:
Water column mm (ISO 20811)	



Damaceno & Antunes
Rua da Alegria 387,
4475-310 Milheirós - Maia
+351229059160 info@damaceno-antunes.pt

TECHNICAL FABRIC DETAILS

SIRA




The Sira curtain combines elegance and functionality in a single product. With a width of 330 cm, it is ideal for covering window surfaces, providing a continuous and sophisticated look. Made of 100% POL FR, this curtain not only offers the beauty of a linen appearance but also ensures safety thanks to its flame-retardant composition.



Article specification

Width	330 cm
Horizontal repeat cm	PLAIN
Vertical repeat cm	PLAIN
Composition	100%POL FR
Weight	135 g/m ²
Thickness (mm)	

Cleaning Instructions



Use Code

Curtains

Environmental Standards

FR Standards

EN 13773

Finish

Optional Fabric Treatment

Mechanical Performance

Abrasion Test / Martindale Rubs (EN ISO 12947-1,2)	
Piling Test (EN ISO 12945-2)	
Colour Fastness to light (ISO 105-B02-2)	4-5
Colour fastness to dry rub (EN ISO 105-X12)	Dry: Wet:
Tearing strength (ISO 13937-3)	Warp: Weft:
Tensile Strenght (EN ISO 13934-1)	Warp: Weft:
Colour fastness to artificial weathering (ISO 105-B04)	
Seam slippage (ISO 13936-2)	Warp: Weft:
Colour fastness to chlorinated water (ISO 105-E03)	
Ultraviolet protection factor UPF (AZ/NZS 4399/1996)	
Spray test (ISO 24920)	
Shrinkage to washing (ISO 5077:2007)	Warp: Weft:
Water column mm (ISO 20811)	